

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Problem Image Mailbox.**

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 02009944 A

(43) Date of publication of application: 12 . 01 . 90

(51) Int. Cl.

F02M 51/00

F02M 61/20

(21) Application number: 63160359

(71) Applicant: NIPPON DENSO CO LTD

(22) Date of filing: 27 . 06 . 88

(72) Inventor: IWANAGA TAKASHI

(54) FUEL INJECTION DEVICE

COPYRIGHT: (C)1990 JPO&Japic

(57) Abstract:

PURPOSE: To gradually increase the volume of a control chamber and properly suppress the initial injection rate by integrally moving a control valve body via a projection as a valve body communicating or cutting off the control port and the discharge port of a three-way solenoid valve is opened.

CONSTITUTION: When a current is fed to a solenoid coil 49, an armature 39 is attracted by a core 47, an outer valve 36 serving as a valve body is raised, a poppet section 37 is released from the first valve seat 34, thus a control port Y and a discharge port Z are communicated, fuel is injected through a nozzle not shown in the figure. When the outer valve 36 is further raised, the second valve seat 43 is pressed to a poppet section 46, thus a feed port X and the control port Y are cut off. As the outer valve 36 is raised, a control valve body 9 is kept in contact with a projection 38 by the pressure difference between pressures applied to its front and back and the energizing force of a return spring and raised together with the outer valve 36. The volume of a control chamber 8 is gradually increased.

